

```

1
2
3 /**
4  * 2022.05.10
5  * 작성자 : 강건일
6  * main.c
7  */
8
9 #include "F28x_Project.h"
10
11 #define SW2_STATE    GpioDataRegs.GPBDAT.bit.GPIO41
12 #define SW3_STATE    GpioDataRegs.GPBDAT.bit.GPIO45
13
14 #define BLU_LED_HIGH    GpioDataRegs.GPASET.bit.GPIO31=1    //
15 #define BLU_LED_LOW    GpioDataRegs.GPACLEAR.bit.GPIO31=1    //
16
17 #define RED_LED_HIGH    GpioDataRegs.GPBSET.bit.GPIO34=1    //
18 #define RED_LED_LOW    GpioDataRegs.GPBCLEAR.bit.GPIO34=1    //
19
20 #define GRN_LED_HIGH    GpioDataRegs.GPBSET.bit.GPIO44=1    //
21 #define GRN_LED_LOW    GpioDataRegs.GPBCLEAR.bit.GPIO44=1    //
22
23 #define L2_LED_HIGH    GpioDataRegs.GPBSET.bit.GPIO38=1
24 #define L2_LED_LOW    GpioDataRegs.GPBCLEAR.bit.GPIO38=1    //
25
26 #define L0_LED_HIGH    GpioDataRegs.GPBSET.bit.GPIO37=1    //
27 #define L0_LED_LOW    GpioDataRegs.GPBCLEAR.bit.GPIO37=1    //
28
29 #define L1_LED_HIGH    GpioDataRegs.GPBSET.bit.GPIO40=1    //
30 #define L1_LED_LOW    GpioDataRegs.GPBCLEAR.bit.GPIO40=1    //
31
32 #define L3_LED_HIGH    GpioDataRegs.GPBSET.bit.GPIO39=1    //
33 #define L3_LED_LOW    GpioDataRegs.GPBCLEAR.bit.GPIO39=1    //
34
35 #define L4_LED_HIGH    GpioDataRegs.GPBSET.bit.GPIO43=1    //
36 #define L4_LED_LOW    GpioDataRegs.GPBCLEAR.bit.GPIO43=1    //
37
38 #define L5_LED_HIGH    GpioDataRegs.GPCSET.bit.GPIO67 = 1 //
39 #define L5_LED_LOW    GpioDataRegs.GPCCLEAR.bit.GPIO67 = 1
40
41 #define L6_LED_HIGH    GpioDataRegs.GPBSET.bit.GPIO47=1    //
42 #define L6_LED_LOW    GpioDataRegs.GPBCLEAR.bit.GPIO47=1    //
43
44 #define L7_LED_HIGH    GpioDataRegs.GPBSET.bit.GPIO46=1    //
45 #define L7_LED_LOW    GpioDataRegs.GPBCLEAR.bit.GPIO46=1    //
46
47 #define REFERENCE_VDAC  0
48 #define REFERENCE_VREF  1
49
50 #define setup  100
51
52 interrupt void cpu_timer1_isr(void);
53 void InitDacModules(void);
54 void InitEPwmModules(void);
55 void InitAdcModule(void);
56 __interrupt void MainIsr(void);
57
58 Uint16 BackTicker;
59 Uint16 IsrTicker;
60
61 int main(void)
62 {

```

```

63 // Step 1. Initialize System Control:
64 // PLL, WatchDog, enable Peripheral Clocks
65 // This example function is found in the F2837xD_SysCtrl.c file.
66
67     InitSysCtrl();
68
69 #ifndef _FLASH
70     InitFlash();
71 #endif
72
73 // Step 2. Initialize GPIO:
74 // This example function is found in the F2837xD_Gpio.c file and
75 // illustrates how to set the GPIO to it's default state.
76
77     InitGpio(); // Skipped for this example
78     EALLOW;
79
80     GpioCtrlRegs.GPADIR.bit.GPIO31 = 1; //Blu
81     GpioCtrlRegs.GPBDIR.bit.GPIO34 = 1; //Red
82     GpioCtrlRegs.GPBDIR.bit.GPIO38 = 1; //L2
83     GpioCtrlRegs.GPBDIR.bit.GPIO44 = 1; //Grn
84     GpioCtrlRegs.GPCDIR.bit.GPIO67 = 1; //L5,
85     GpioCtrlRegs.GPBDIR.bit.GPIO37 = 1; //L0,
86     GpioCtrlRegs.GPBDIR.bit.GPIO47 = 1; //L6,
87     GpioCtrlRegs.GPBDIR.bit.GPIO40 = 1; //L1,
88     GpioCtrlRegs.GPBDIR.bit.GPIO39 = 1; //L3,
89     GpioCtrlRegs.GPBDIR.bit.GPIO43 = 1; //L4,
90     GpioCtrlRegs.GPBDIR.bit.GPIO46 = 1; //L7,
91
92     GPIO_SetupPinOptions(31, GPIO_OUTPUT, GPIO_PUSHPULL);
93     GPIO_SetupPinMux(31, GPIO_MUX_CPU1, 0);
94     GPIO_SetupPinOptions(34, GPIO_OUTPUT, GPIO_PUSHPULL);
95     GPIO_SetupPinMux(34, GPIO_MUX_CPU1, 0);
96     GPIO_SetupPinOptions(38, GPIO_OUTPUT, GPIO_PUSHPULL);
97     GPIO_SetupPinMux(38, GPIO_MUX_CPU1, 0);
98     GPIO_SetupPinOptions(44, GPIO_OUTPUT, GPIO_PUSHPULL);
99     GPIO_SetupPinMux(44, GPIO_MUX_CPU1, 0);
100    GPIO_SetupPinOptions(37, GPIO_OUTPUT, GPIO_PUSHPULL); //cpu1, L0
101    GPIO_SetupPinMux(37, GPIO_MUX_CPU1, 0);
102    GPIO_SetupPinOptions(40, GPIO_OUTPUT, GPIO_PUSHPULL); //cpu1, L1
103    GPIO_SetupPinMux(40, GPIO_MUX_CPU1, 0);
104    GPIO_SetupPinOptions(39, GPIO_OUTPUT, GPIO_PUSHPULL); //cpu1, L3
105    GPIO_SetupPinMux(39, GPIO_MUX_CPU1, 0);
106    GPIO_SetupPinOptions(43, GPIO_OUTPUT, GPIO_PUSHPULL); //cpu1, L4
107    GPIO_SetupPinMux(43, GPIO_MUX_CPU1, 0);
108    GPIO_SetupPinOptions(67, GPIO_OUTPUT, GPIO_PUSHPULL); //cpu1, L5
109    GPIO_SetupPinMux(67, GPIO_MUX_CPU1, 0);
110    GPIO_SetupPinOptions(47, GPIO_OUTPUT, GPIO_PUSHPULL); //cpu1, L6
111    GPIO_SetupPinMux(47, GPIO_MUX_CPU1, 0);
112    GPIO_SetupPinOptions(46, GPIO_OUTPUT, GPIO_PUSHPULL); //cpu1, L7
113    GPIO_SetupPinMux(46, GPIO_MUX_CPU1, 0);
114    GPIO_SetupPinOptions(41, GPIO_INPUT, GPIO_QUAL6); //cpu1 sw2 input
115    GPIO_SetupPinMux(41, GPIO_MUX_CPU1, 0);
116    GPIO_SetupPinOptions(45, GPIO_INPUT, GPIO_QUAL6); //cpu1 sw3 input
117    GPIO_SetupPinMux(45, GPIO_MUX_CPU1, 0);
118    //
119    EDIS;
120
121    GpioDataRegs.GPADAT.bit.GPIO31 = 1;
122    GpioDataRegs.GPBDAT.bit.GPIO38 = 1; //L2
123    GpioDataRegs.GPBDAT.bit.GPIO44 = 1; // Grn
124    GpioDataRegs.GPBDAT.bit.GPIO34 = 1; // Red

```

```

125
126     GpioDataRegs.GPBDAT.bit.GPIO37 = 1; //L0,
127     GpioDataRegs.GPBDAT.bit.GPIO47 = 1; // L6 ,
128     GpioCtrlRegs.GPCDIR.bit.GPIO67 = 1; // L5,
129     GpioDataRegs.GPBDAT.bit.GPIO40 = 1; //cpu1 L1,
130
131     GpioDataRegs.GPBDAT.bit.GPIO39 = 1; //L3
132     GpioDataRegs.GPBDAT.bit.GPIO43 = 1; //L4
133     GpioDataRegs.GPBDAT.bit.GPIO46 = 1; //L7
134     //
135     // Step 3. Clear all interrupts and initialize PIE vector table:
136     // Disable CPU interrupts
137     //
138     DINT;
139
140     // Initialize the PIE control registers to their default state.
141     // The default state is all PIE interrupts disabled and flags
142     // are cleared.
143     // This function is found in the F2837xD_PieCtrl.c file.
144     //
145     InitPieCtrl();
146     //
147     // Disable CPU interrupts and clear all CPU interrupt flags:
148     //
149     IER = 0x0000;
150     IFR = 0x0000;
151     //
152     // Initialize the PIE vector table with pointers to the shell Interrupt
153     // Service Routines (ISR).
154     // This will populate the entire table, even if the interrupt
155     // is not used in this example. This is useful for debug purposes.
156     // The shell ISR routines are found in F2837xD_DefaultIsr.c.
157     // This function is found in F2837xD_PieVect.c.
158     //
159     InitPieVectTable();
160
161     // Enable global Interrupts and higher priority real-time debug events:
162     //
163     EINT; // Enable Global interrupt INTM
164     ERTM; // Enable Global realtime interrupt DBGEM
165
166     EALLOW;
167
168     PieVectTable.ADCB1_INT = &MainIsr; // Interrupt Service Routine Re-mapping
169
170     EDIS;
171
172     PieCtrlRegs.PIEIER1.bit.INTx2 = 1; // Enable PIE group 1 interrupt 1 for
ADCB1_INT
173     IER |= M_INT1;
174
175     // Step 6. IDLE loop. Just sit and loop forever (optional):
176
177     InitEPwmModules(); // Initialize EPWM Modules //210914
178     InitDacModules(); // Initialize DAC Modules
179     InitAdcModule(); // Initialize On-Chip ADC Module
180
181     // Step 7
182     // 7.1 Initialize S/W modules and Variables //210914
183     BackTicker = 0;
184     IsrTicker = 0;
185

```

```

186         // Step 8
187         // 8.1 Enable Global real-time interrupt DBGMC
188         // 8.2 Enable Global Interrupt
189
190         EINT;    // Enable Global interrupt INTM
191         ERTM;    // Enable Global real-time interrupt DBGMC
192
193         // Step 9
194         // 9.1 Idle Loop
195
196         int j ;
197         for (j = 0; j < setup ; j++) // 실측정:150ms on/off
198         {
199
200             RED_LED_LOW ; // LOW 일때 켜짐
201             BLU_LED_LOW ; // LOW 일때 켜짐
202             GRN_LED_LOW ;
203             L0_LED_LOW ;
204             L1_LED_LOW ;
205             L2_LED_LOW ;
206             L3_LED_LOW ;
207             L4_LED_LOW ;
208             L5_LED_LOW ;
209             L6_LED_LOW ;
210             L7_LED_LOW ;
211
212             DELAY_US(100000); //
213
214             RED_LED_HIGH ;
215             BLU_LED_HIGH ;
216             GRN_LED_HIGH ;
217             L0_LED_HIGH ;
218             L1_LED_HIGH ;
219             L2_LED_HIGH ;
220             L3_LED_HIGH ;
221             L4_LED_HIGH ;
222             L5_LED_HIGH ;
223             L6_LED_HIGH ;
224             L7_LED_HIGH ;
225             DELAY_US(100000);
226         }
227
228         for(;;)
229         {
230             L4_LED_LOW ;
231             DELAY_US(10);
232
233             BackTicker++; //
234
235             if (SW2_STATE) // switch 2 off (HIGH)
236             {
237
238                 if(SW3_STATE) // 스위치 모두 OFF,
239                 {
240                     GRN_LED_LOW ; // GRN LED ON
241                     RED_LED_HIGH ;
242                     BLU_LED_HIGH ;
243
244                     DELAY_US(10);
245
246                 } //switch 모두 off, sw3 동작 끝
247

```

```

248         else // switch 3 만 on (LOW),BLUE on
249         {
250             GRN_LED_HIGH ; //GRN OFF
251             RED_LED_HIGH ; //
252             BLU_LED_LOW ; // BLUE ON low 일때 켜짐,
253
254             DELAY_US(10);
255             } //blue 의 if 문 끝
256             } //if sw2 끝
257
258         else if (SW3_STATE) // switch2 on, switch 3 off (HIGH), RED LED
259         {
260             GRN_LED_HIGH ;
261             RED_LED_LOW ; // ON low 일때 켜짐, RED led 켜짐
262             BLU_LED_HIGH ;
263
264             DELAY_US(10);
265
266             } //sw2 Red else if 의 끝 END
267
268         else // 30spk 실험220325: 스위치 모두 ON, LED 모두 켜짐
269         {
270             GRN_LED_LOW ;
271             RED_LED_LOW ;
272             BLU_LED_LOW ;
273
274             DELAY_US(10);
275
276             } //처음 else switch2
277
278         L4_LED_HIGH ;
279         DELAY_US(10);
280
281     } //end of for
282     } // end of main
283 // Step 10
284 // 10.1 Local Interrupt Service Routines & Functions
285
286 __interrupt void MainIsr(void)
287 {
288     IsrTicker++;
289
290     L5_LED_LOW ; //L5 켜짐, 주기확인용
291
292     // Clear INT flag and Acknowledge to receive more interrupts
293     AdcbRegs.ADCINTFLGCLR.bit.ADCINT1 = 1; // Clear INT1 flag
294     PieCtrlRegs.PIEACK.bit.ACK1 = 1; // Acknowledge this interrupt to receive more
295     interrupts from group 1
296
297     DELAY_US(10);
298     L5_LED_HIGH ; //L5 꺼짐,
299     DELAY_US(10);
300
301     } //Main Isr 끝
302
303 void InitDacModules(void)
304 {
305     EALLOW;
306     DacbRegs.DACCTL.bit.DACREFSEL = REFERENCE_VREF ;
307     DacbRegs.DACCTL.bit.DACREFSEL = REFERENCE_VREF;

```

```

308     DaccRegs.DACCTL.bit.DACREFSEL = REFERENCE_VREF;
309
310     DaccRegs.DACOUTEN.bit.DACOUTEN = 1;    // Enable DAC-A output
311     DaccRegs.DACOUTEN.bit.DACOUTEN = 1;    // Enable DAC-B output
312     DaccRegs.DACOUTEN.bit.DACOUTEN = 1;
313     EDIS;
314
315     DaccRegs.DACVALS.bit.DACVALS = 0; // Clear DAC-A value register
316     DaccRegs.DACVALS.bit.DACVALS = 0; // Clear DAC-B value register
317     DaccRegs.DACVALS.bit.DACVALS = 0;
318 }
319
320 void InitEPwmModules(void)
321 {
322
323     EALLOW;
324     CpuSysRegs.PCLKCR0.bit.TBCLKSYNC = 0;
325     EDIS;
326
327     EALLOW;
328     ClkCfgRegs.PERCLKDIVSEL.bit.EPWMCLKDIV = 0;
329     EDIS;
330
331     // Setup Counter Mode and Clock
332     EPwm1Regs.TBCTL.bit.CTRMODE = 2;    // Count Up and Down (Symmetric)
333     EPwm1Regs.TBCTL.bit.HSPCLKDIV = 0;    // TBCLK = (SYSCLKOUT / EPWMCLKDIV) /
(HSPCLKDIV * CLKDIV) = 200MHz
334     EPwm1Regs.TBCTL.bit.CLKDIV = 0;
335
336     // Setup Period (Carrier Frequency)
337
338     EPwm1Regs.TBPRD = 5000;    // Set Timer Period, (200MHz/20KHz)/2 = 5,000, sampling
20khz
339
340     EPwm1Regs.TBCTR = 0;    // Clear Counter
341
342     // Set up Event Trigger(SOC) with CNT_zero enable for Time-base of EPWM1
343     EPwm1Regs.ETSEL.bit.SOCAEN = 1;    // Enable SOCA
344     EPwm1Regs.ETSEL.bit.SOCASEL = 1;    // Enable CNT_zero event for SOCA
345     EPwm1Regs.ETPS.bit.SOCAPRD = 1;    // Generate SOCA on the 1st event
346     EPwm1Regs.ETCLR.bit.SOCA = 1;    // Clear SOCA flag
347
348     EALLOW;
349     CpuSysRegs.PCLKCR0.bit.TBCLKSYNC = 1;
350     EDIS;
351 }
352
353 void InitAdcModule(void)
354 {
355     // Initialize ADC-B module
356     EALLOW;
357     AdcbRegs.ADCCTL2.bit.PRESCALE = 14;    // Set ADCCLK divider to /8 (25MHz @ 200MHz
SYSCLKOUT)
358     AdcSetMode(ADC_ADCB, ADC_RESOLUTION_12BIT, ADC_SIGNALMODE_SINGLE);
359     AdcbRegs.ADCCTL1.bit.INTPULSEPOS = 1;    // Set pulse positions to late
360     AdcbRegs.ADCCTL1.bit.ADCPWDNZ = 1;    // Power up the ADC
361     DELAY_US(1000);    // Delay for 1ms to allow ADC time to power up.
362     EDIS;
363
364     // Initialize ADC-D module,210726 add
365     EALLOW;
366     AdcdRegs.ADCCTL2.bit.PRESCALE = 14;    // Set ADCCLK divider to /8 (25MHz @ 200MHz

```

```

SYSCLKOUT)
367     AdcSetMode(ADC_ADCD, ADC_RESOLUTION_12BIT, ADC_SIGNALMODE_SINGLE);
368     AdcdRegs.ADCCTL1.bit.INTPULSEPOS = 1;    // Set pulse positions to late
369     AdcdRegs.ADCCTL1.bit.ADCPWDNZ = 1;      // Power up the ADC
370     DELAY_US(1000);                          // Delay for 1ms to allow ADC time to power
up. 170727 2ms 개선 안됨
371     EDIS;
372
373     // Configuration ADC module
374     EALLOW;
375     AdcbRegs.ADCSOC0CTL.bit.CHSEL = 0;        // B0,VDAC,  ADC-B SOC0 : ADCINB0, Variable
Voltage Input (Controlled by Potentiometer)
376     AdcbRegs.ADCSOC0CTL.bit.ACQPS = 14;      // Sample and hold time : (14 + 1) SYSCLK =
75nsec
377     AdcbRegs.ADCSOC0CTL.bit.TRIGSEL = 5;      // Trigger source : EPWM1, ADCSOCA
378
379     AdcbRegs.ADCSOC1CTL.bit.CHSEL = 2;        // B2, Sensor2, ADC-B SOC1 : ADCINB2, Variable
Voltage Input (Controlled by Potentiometer) //170203 addB2
380     AdcbRegs.ADCSOC1CTL.bit.ACQPS = 14;      // Sample and hold time : (14 + 1) SYSCLK =
75nsec //170203 addB2
381     AdcbRegs.ADCSOC1CTL.bit.TRIGSEL = 5;      // Trigger source : EPWM1, ADCSOCA //170203
addB2
382
383     AdcbRegs.ADCSOC2CTL.bit.CHSEL = 3;        // B3, sensor1, ADC-B SOC2 : ADCINB3, Variable
Voltage Input (Controlled by Potentiometer) //191206 add B3
384     AdcbRegs.ADCSOC2CTL.bit.ACQPS = 14;      // Sample and hold time : (14 + 1) SYSCLK =
75nsec
385     AdcbRegs.ADCSOC2CTL.bit.TRIGSEL = 5;      // Trigger source : EPWM1, ADCSOCA
386
387     //210726 add for D_Channel
388     AdcdRegs.ADCSOC3CTL.bit.CHSEL = 0;        // D0, FIR IN, ADC-B SOC3 : ADCIND0, Variable
Voltage Input (Controlled by Potentiometer) //191206 add B3
389     AdcdRegs.ADCSOC3CTL.bit.ACQPS = 14;      // Sample and hold time : (14 + 1) SYSCLK =
75nsec
390     AdcdRegs.ADCSOC3CTL.bit.TRIGSEL = 5;      // Trigger source : EPWM1, ADCSOCA
391
392     AdcbRegs.ADCINTSEL1N2.bit.INT1SEL = 0;    // End of SOC0 will set INT1 flag
393     AdcbRegs.ADCINTSEL1N2.bit.INT1E = 1;     // Enable INT1 flag
394     AdcbRegs.ADCINTFLGCLR.bit.ADCINT1 = 1;   // Make sure INT1 flag is cleared
395     EDIS;
396     }
397     // END
398 //
399 // End of file
400 //
401
402

```